

Index: Q07

Corner: C-S 1/16

LAND CORNER RECORD

State of Indiana
Hoosier National Forest

Polk_G16

Township: 7N

Range: 1E


Section: 20 2nd P.M.

County: MONROE CO.


EXISTING SURVEYS

Original Government Survey				Original Survey Evidence Found			
Year Surveyed:		By:		Date of Search:		By:	
Original Monument:				Monument Found:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded: Surveyors Office				Year Searched: By:			
Book: Page: Date:				Monument Found			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance

OTHER EVIDENCE

Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc. The monument is located 12' north of an east-west fence line and in a north-south fence line, about 150' south of a creek, there is a small draw about 50' west and 100' east.	Sketch of Monument 
--	--

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position. Center South 1/16; A 0.3'x0.8' sandstone was found 0.3' above grade. This corner was most likely established on a 1891 Legal Survey found in Survey Book 2, page 183-184 by Alexander Spencer. Although Mr. Spencer does not call out this corner, he does indicate that he measures from the Center of Section to the South 1/4 corner.	
Corner Diagram 	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence. 10"-12" Triple Maple N85°W 44.0' 6" Pignut Hickory N60°E 20.2' 14" Beech S65°W 16.5'
Corner Recordation:	Certificate Prepared:
Filed and Recorded in County records:	Date:
Book:	Page:
Geodetic Coordinates:	Lat./N.
Section: 20	Long./E.
Edited By: BTR	Date Created: 10/2004

Referenced on BRG survey recorded as InstNo.2005011737.

Accepted by the Monroe County Surveyor Review Board on August 6, 2019.

Index: Q-7 Corner: CS1/16 LAND CORNER RECORD

State of Indiana
Hoosier National Forest

Twnshp: 7N Range: 1E Section: 20 2nd P.M. County Monroe

EXISTING SURVEYS

Original Government Survey


Original Survey Evidence Found

Year Surveyed:				By:			
Original Monument:				Date of Search:			
Species	Diameter	Bearing	Distance	Monument Found:			
				Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded:	Unknown			Year Searched:	11/4/03	By:	B. Stone
Book:	Page:	Date:		Monument Found	9" x 5" stone with a + on top, standing firmly 1" above the ground under a 3 strand barbwire fence		
Monument Set:				Species	Diameter	Bearing	Distance

OTHER EVIDENCE

Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc.	Sketch of Monument
The stone is located on a northeast slope 12 feet north and downhill from a east-west-north fence intersection where a gray 3 foot tall wooden box is attached to the metal fence. The box holds a battery to energize the electric fence running west. Roberts Road is approximately 400 feet east. A white house trailer is approximately 220 feet N 28°E and a sandstone house is approximately 300 feet S 29°E. A 12 foot x 10 wooden shed foot is S 19°W 60 feet. All can be seen from the stone. South of the east-west fence is an open pasture. Open woods north of the fence lies northeast and northwest of the stone.	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.			
			
Left as found.			
Corner Diagram	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.		
	Hickory 22" N 75°E 7.0 Ft. W. Oak 38" S 46° W 16.3 Ft.		
	Corner Recordation:		Certificate Prepared:
	Filed and Recorded in County records:		Date:
	Book:		Page:
	Geodetic Coordinates:		Lat./N.
Section: 20	Edited By: Robert J. Stone		Date Created: 12/5/03